

Side Mounting Liquid Level Switches

Features



- Low cost
- Stainless steel version suitable for most fluids

Specification

Contact Rating	50VA AC/DC
Contact Resistance	200mW
Dialectric Strength	600Vdc
Max. Switching Voltage	350Vdc / 300Vac
Max. Switching Current:	
LS-SN1 & SN2	0.5A DC/AC
LS-SS1 & SS1	1.0A DC/AC
Insulation resistance	10 MW
Max. Temp:	
LS-SN1 & SN2	80°C
LS-SS1 & SS2	120°C
Max. Pressure:	
LS-SN1 & SN2	1.9bar
LS-SS1 & SS2	4.9bar
Installation Category	IEC 664 Category II
Pollution Degree	IEC 664 Degree 1
Shock Resistance	20G
Specific Gravity Of Float	0.7
Flying Lead Length	Approx. 50 cm
Country Of Origin	China

Product Codes

LS-SN1

Polypropylene float switch M16, internal fixing

LS-SN2

Polypropylene float switch 1/2" NPT, external fixing

LS-SS1

Stainless steel float switch M16, internal fixing

LS-SS2

Stainless steel float switch 1/2" PF, external fixing

Technical Overview

The LS-S range of side mounting level switches designed for high or low liquid level detection in tanks and vessels. Units consist of a lever arm reed switch assembly and a tank fixing boss.

Type 1 switches fit from the inside of the tank and tighten onto a back nut on the outside face.

Type 2 switches mount from the outside into a boss and access to inside face is not required.

Units project into the tank by a maximum of 100mm.

Installation

The switch should be installed by suitably qualified personnel only. Electrical termination should be carried out by a suitably qualified electrician in accordance with prevailing regulations.

Internal mounting switches must be passed through a 16mm hole in the side of the vessel and secured on the outside using the nut provided. Care should be taken not to over tighten the nut particularly in the case of nylon variants.

External mounting switches are fixed into a suitable boss using a suitable sealing compound if necessary.

In all cases, it will be necessary to ensure that the switch is mounted in the correct orientation for the required application.